TITLE OF THE INVENTION

LIGHT TRANSMITTER AND OPTICAL TRANSFER SYSTEM

BACKGROUND OF THE INVENTION

1. Field of the Invention

This application is based upon and claims the benefit of priority from the prior Japanese Patent Application No. 2001-038022, filed February 15, 2001, the entire contents of which are incorporated herein by reference.

2. Description of the Related Art

The present invention relates to a slave station-to-master station upward link that achieves high-quality data transfer in an optical transfer system for interconnecting a master station and a plurality of slave stations by an optical fiber.

Passive optical network systems attract much attention because they use an optical fiber, thus accommodating a subscriber's home of a fiber-to-user system in a control station (master station). (Representative examples of fiber-to-user systems are an FTTH (Fiber-To-The-Home) system, a portable phone, a radio base station (slave station) of an ITS (Intelligent Transport Systems), and the like.) The passive optical network technology is useful, simplifying and miniaturizing a transfer system. This is because the technology can be combined with the sub-carrier multiplexing technology so that a master

station needs only one pair of optical transceivers and can yet perform transmission and reception with a plurality of slave stations at a time. The passive optical network system, however, generates optical beat noise when the optical signals sent from the plurality of slave stations interfere with each other on an upward link from the slave stations to the master station. FIG. 1 is a graph explaining optical beat noise. The optical beat noise is a noise component of an information signal received at the master station. It develops, as shown in FIG. 1B, in a frequency band that corresponds to a wavelength difference $\Delta \lambda$ between optical signals A and B output from a plurality of slave stations, when the master station receives these signals at a time as shown in FIG. 1A. If the optical signals output from the slave stations are similar in wavelength, that is, if $\Delta \lambda$ is small, optical beat noise develops near the information signal band (e.g., radio frequency band around 1GHz or so). The optical beat noise deteriorates the transfer quality. To solve this problem, there have been proposed some methods.

Published Japanese Patent No. 3096694, for example, proposes a method of providing a noise detector at a master station. The noise detector detects presence/absence of optical beat noise. Thus, the wavelength of a light source at each slave station can be controlled to a predetermined value, thereby to

preserve the transfer quality of a sub-carrier multiplexing signal. In this wavelength control method, the exothermic/endothermic effects of a Peltier heat source element is utilized to control the temperature

5   of a laser diode provided in the slave station. The temperature control stabilizes the wavelength at a predetermined value. This method, wherein the exothermic/endothermic effects control the temperature, is disadvantageous in some respects. First, the

10   control system is liable to oscillate due to a difference in heat transfer between the individual elements, including a laser diode package provided in the slave station. Secondly, it takes rather a long time for the temperature to become stable. Inevitably,

15   the wavelength fluctuates, generating optical beat noise in some cases.

A Peltier element is usually applied to a device for controlling the temperature generated by the exothermic/endothermic effects. If the laser diode

20   package is of a butterfly type, it may contain the laser diode and the Peltier element. However, the butterfly type package requires a space for disposing pins and is expensive. To reduce the size and manufacturing cost of the light transmission section,

25   it is desirable to employ a coaxial type or a Mini-DIL (Minimum Dual-In-Line) type that has a simple configuration of packaging only the laser diode. A

simple, coaxial Mini-DIL type package is sealed from the beginning. Therefore, a Peltier element cannot be incorporated into the package and must be mounted externally to the laser diode package. It is, however,

5 difficult to sufficiently seal the externally mounted Peltier element and the packaged laser diode. Dewdrops may be formed on the Peltier element, due to intrusion of air. The Peltier element may be short-circuit, possibly to deteriorate the long-term reliability of

10 the laser diode package.

BRIEF SUMMARY OF THE INVENTION

An object of the present invention is to provide a light transmitter and optical transfer system that solves the above problems by suppressing the influence

15 by optical beat noise on an upward link of a passive optical multiplex access system between a master station and a plurality of slave stations.

The light transmitter of this invention comprises a packaged laser diode (11) having a first thermal

20 contacting portion that can thermally come in contact with the outside, and a heat source (17) of only the exothermic effect that is provided on the first thermal contacting portion and that has a second thermal contacting portion capable of coming in thermal contact

25 with the outside.

With the present invention it is possible to suppress the influence of the optical beat noise on the

transfer quality by using a simple method of
controlling the wavelength of an optical signal based
on a unidirectional temperature change of only the
exothermic effect (not of the endothermic effect).

5   Since wavelength control involves unidirectional
temperature control, the control system is not liable
to oscillate. The system can therefore reliably
control the wavelength, regardless of an individual
difference in heat transfer of the laser diode package.

10   By using an exothermic-effect only as heat source, no
dewdrops will be formed. This imparts a long-term
reliability to the laser diode package. Furthermore,
the wavelength controller has such a structure that
needs only unidirectional temperature control. The

15   circuit scale of the controller can be reduced to
almost a half the scale of the conventional wavelength
controller that has both exothermic effect and
endothermic effect. The present invention, therefore,
is useful in miniaturizing the slave stations.

20   Moreover, the wavelength control method of the present
invention can be applied to a cost-effective coaxial
type or Mini-DIL type package, too, and can reduce the
costs of the light transmitter.

       Furthermore, the laser diode may undergo prolonged

25   wavelength fluctuation, due to various factors such as
an ambient temperature, aging, and the like.
Conventionally, optical beat noise is always monitored

in the master station to control the wavelengths of the slave stations to a preset value by using the exothermic and endothermic effects. The noise is so monitored in order to avoid the influence of the

5 optical beat noise on the transfer quality against the fluctuation of wavelength. The influence of the optical beat noise can be avoided if there is provided a sufficient inter-wavelength spacing. Therefore, as in the present invention, a simple unidirectional

10 wavelength control method can be performed to change the wavelength by using only a heat source. This provides an appropriate inter-wavelength spacing, preventing the generation of the optical beat noise. With the present invention it is possible to

15 miniaturize the configuration of a transfer system as a simple control system to thereby enhance the reliability of the transfer system not only at the time of initial introduction but also for a prolonged term.

Furthermore, the temperature may remarkably rise

20 around the laser diode, depending on the weather, at a slave station that is positioned outdoors, like a radio base station. In the present invention, the master station monitors the temperature of the laser diode provided in the slave station, and a desirable

25 wavelength is preset on the basis of the temperature monitored. The wavelength is therefore controlled in a fewer steps than otherwise, readily preventing optical

beat noise.

Generally, a large-power transistor is used to drive a heating element such as a heater. The large-power transistor can be a heating element, however. Hence, any heating device comprising a heater and a large-power transistor has two heat-generating parts. In the present invention, the transistor is a sole heat-generating element, which can heat the laser diode efficiently. As will be described later in "DETAILED DESCRIPTION OF THE INVENTION," it suffices to impart a slight temperature change of a few degrees Centigrade, to the laser diode in the present invention. Thus, a small transistor with a little power dissipation can control the wavelength to avoid the occurrence of optical beat noise. Furthermore, the transistor is sealed and is not oxidized.

Furthermore, the laser diode provided in the coaxial type package used in the present invention can transfer heat to a flange to easily change the temperature of the laser diode in the package. The flange has a relatively large area and can improve the heat transfer efficiency. The flange therefore serves to change temperature, while preventing power dissipation. Moreover, the coaxial type package is simpler in configuration and less expensive than the butterfly type package.

The present invention utilizes both an optical

sub-carrier multiplexing access and a passive optical
network. This enables each slave station to transfer a
CW (Continuous Wave) optical signal to the master
station even if no information signals are is present.

5   Optical beat noise can therefore be always monitored.
Even in such a system that transfers a busting
modulation signal like a radio signal, the optical beat
noise can be always suppressed to preserve a high
transfer quality.

10   In the present invention, a simple method of
controlling the wavelength of an optical signal in
accordance with an exothermic-effect-only
unidirectional temperature change can be employed to
suppress the influence of the optical beat noise on the

15   transfer quality. Wavelength control involves
unidirectional temperature control. Therefore, the
control system is not liable to oscillate, enabling
controlling the wavelength in a stable manner
independently of an individual difference in heat

20   transfer including that of the laser diode package.
The exothermic-effect-only wavelength control of this
invention can be applied even to a laser diode
contained in a coaxial type or Mini-DIL type package
that cannot be integrated with a Peltier element and

25   can reduce the manufacturing cost of the optical
transfer section. The wavelength controller such a
small circuit only needs unidirectional temperature

control. The size of the controller can therefore be reduced to almost half the size of the conventional wavelength controller that utilizes both the exothermic and endothermic effects. The present invention,

5   therefore, is useful also in miniaturizing the slave stations.

Furthermore, in a passive optical network, the wavelengths of the slave stations need not be evenly spaced from each other but only need to have an inter-

10   wavelength spacing of at least 0.16 nm. A small transistor of less power dissipation may be used as a heat-generating element, instead of a large-scale heater or the like. If so, heat generation will take place at one point only. In this case, the laser diode

15   is heated efficiently. Moreover, dewdrops will not form on the transistor, which is completely sealed.

The present invention can therefore provide a wavelength control system that has a high reliability for a long term, that has a simple configuration, and

20   that can save power dissipation efficiently.
BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

FIGS. 1A and 1B are graphs for explaining optical beat noise;

FIG. 2 is a schematic block diagram for showing an

25   optical transfer system according to a first embodiment of the present invention;

FIG. 3 is a schematic block diagram for showing a

wavelength controller 18;

FIG. 4 is a circuit diagram for showing the wavelength controller 18 where a transistor is used as an exothermic-effect-only heat source;

FIG. 5 is a schematic configuration diagram for showing a light transmitter 10 where a coaxial type package is used to contain a laser diode;

FIG. 6 is a schematic configuration diagram for showing the light transmitter 10 where a Mini-DIL type package is used to contain the laser diode;

FIG. 7 is a schematic block diagram for showing the optical transfer system according to a second embodiment of the present invention;

FIG. 8 is a schematic block diagram for showing the optical transfer system according to a third embodiment of the present invention;

FIG. 9 is a flowchart for showing a wavelength control algorithm of the present invention; and

FIG. 10 is a graph for showing a relationship between an inter-wavelength spacing and optical beat noise.

DETAILED DESCRIPTION OF THE INVENTION

Embodiments of the present invention will be described, with reference to the drawings. The embodiments comprise three slave stations each. Nonetheless, it suffices if each embodiment has at least two slave stations.

First Embodiment

FIG. 2 shows a schematic block diagram of an optical transfer system according to the first embodiment of the present invention. As FIG. 2 shows, an optical fiber 3 connects a master station 1 to slave stations 2a to 2c. In this embodiment, a downward link from the master station 1 to the slave stations 2 and an upward link from the slave stations 2 to the master station 1 consist of bus type optical fibers 3a and 3b, respectively. They may be replaced by optical fibers of a star type, tree type or even any other type, provided that they serve to construct a passive optical network. The embodiment is described with reference to the upward link, where optical beat noise is a problem. In the slave station 2a, a modulator 9 converts an information signal 100, which is to be transferred to the master station 1, into a modulated signal 101. The signal 101 is applies it to the laser diode 11 provided in a light transmitter 10. The information signal 100 may be a radio signal received at an antenna 12. In this case, the modulator 9 operates as a frequency converter or a level adjuster. The laser diode 11 transfers, to the master station 1, an optical signal 102 which is directly modulated with the modulated signal 101 and has a wavelength λa assigned to the slave station 2a beforehand. Likewise, the slave stations 2b and 2c output optical signals 103 and 104

having wavelengths λb and λc, respectively. These optical signals 102, 103, and 104 are each supplied through an optical coupler 4 to the optical fiber 3b and are optically modulated into optical signals 105.

5 A light receiver 15 provided in the master station 1 receives the optical signals 105, providing a received signal 106. In the master station 1, a demodulator 16 modulates the signal 106, thus receiving the information signal 100 from the slave stations 2. If

10 the respective wavelengths λa, λb, and λc of the optical signals 102, 103, and 105 sent from the slave stations 2 are similar to each other, optical beat noise is generated in a band of the received signal 106. The optical heat noise will deteriorate the transfer

15 quality of the information signal sent from each slave station. It is, therefore, necessary to control the respective wavelengths λa, λb, and λc of the optical signals 102, 103, and 104, prevent the optical beat noise. To this end, each slave station 2 has a

20 wavelength controller 18. FIG. 3 is a schematic block diagram of the wavelength controller 18.

In the slave stations 2, an exothermic-effect-only heat source element 17 is used as wavelength control means for the laser diode 11. The exothermic-effect-

25 only wavelength control method will be described with reference to a proportional control taken for example. As FIG. 3 shows, a heat detector (e.g., thermister) 19

surrounds the laser diode 11 to detect the temperatures
of the exothermic-effect-only heat source 17 and laser
diode 11. The light transmitter 10 comprises the laser
diode 1, the heat source 17, and a thermister 19. A

5   temperature measuring circuit 20 determines the
temperature of the laser diode 11 from a change in the
resistance of the thermister 19. The circuit 20
generates a temperature signal 107 that represents the
temperature thus determined. A comparator circuit 22

10 compares the temperature signal 107 with a preset
temperature value 108 supplied from a temperature
setting device 21 and generates an error signal 109
representing the difference between the signal 108 and
the value 108. The error signal 109 is supplied to a

15 heat source driver circuit 23. The heat source driver
circuit 23 controls the amount of heat that the heat
source 17 generates, in accordance with the magnitude
of the error signal 109, to thereby stabilize the
temperature of the laser diode 11 at the preset

20 temperature value 108. The thermister 19 is adhered to,
for example, the flange of the laser diode 11. It is
so position as to easily detect the temperature of the
laser diode. Preferably, the heat source 17 also is
adhered to the flange of the laser diode 11 to reduce

25 the thermal resistance component and, ultimately, to
decrease the power dissipation. In such exothermic-
effect-only temperature control, λa, λb, and λc can

be controlled not to be similar to each other, by
giving them respective temperature differences. This
measure taken, a temperature stability of 1.0°C or less
is achieved, controlling the wavelength λ of the
5   optical signal 102 output from the laser diode 11 at a
value not larger than 0.1 mm.

FIG. 4 is a circuit diagram of a light transmitter
and a wavelength controller, where a transistor is used
as the exothermic-effect-only heat source 17. A
10   reference voltage V1, resistors R1 and R2, and the
thermister 19 are used to determine the temperature of
the laser diode 11 as packaged. The thermister 19
contacts a thermal contacting portion that can
thermally contact , for example, the flange of the
15   laser diode 11. The thermister 19 is therefore
sensitive to a change in temperature of the laser diode
11 in the package. Moreover, resistors R3, R4, R5, and
R6, a capacitor C, and an operational amplifier are
used to compare the temperature of the laser diode 11
20   and a preset temperature value. The difference signal
representing the difference between the temperature of
the diode 11 and the preset temperature value is
supplied to the base of the heat source transistor 17.
The current flowing in the transistor 17 is changed in
25   accordance with a resistance value of the load resistor
R8 and the difference between the temperature of the
laser diode 11 in the package and the preset

temperature value. The generated heat of the transistor 17 is thereby controlled, whereby the temperature of the laser diode 11 is controlled. The transistor 17 is ordinarily packaged, having a thermal contacting portion that can thermally contact an external device such as a grounding electrode for heat radiation. By mounting the thermal contacting portion of this transistor and the thermal contracting portion that can thermally contact the outside of the laser diode, the temperature of the laser diode 11 can be changed to control the wavelength. Although an NPN transistor is used as the heat source 17, any other electronic circuit device, such as a PNP transistor or an FET, if it generates heat. If the laser diode 11 has a coaxial type package, the anode of the laser diode is often electrically connected to the flange and, hence, to be grounded for stabilization of the operational characteristics thereof. For this purpose, the transistor can be easily mounted in contact with the flange having a relatively large area. Since the flange has good heat transfer properties, a change in temperature can be readily transferred. This helps to change the wavelength with high efficiency.

The embodiment described is a proportional temperature control type. Nonetheless, any other type may be employed in the present invention. For example, an On-Off control type may be used, which can easily

turns the heat source on and off. By On-Off type control, the heat source is turned off if the temperature measurement 107 is higher than the preset temperature value 108, and turned on if the temperature measurement 107 is lower than the preset temperature value 108. Hysteresis may be imparted to the heat source driver circuit 23 by, for example, enhancing the operation sensitivity, a time delay may be imparted to the circuit 23 in consideration of the capacity of the heat source. The heat source is thereby prevented from being turned on and off too frequently. In addition, a pulse interval control type is available, which is a variant of the On-Off control type. In the pulse interval type control method, On/Off switching interval and frequency are changed to achieve control nearly equal to proportional control. Any other temperature control method may be employed.

FIGS. 5 and 6 are schematic configuration diagrams of the light transmitter 10. The transmitter 10 comprises a transistor as the exothermic-effect-only heat source 17. FIG. 5 shows a specific example, in which a coaxial type package 11-a contains the laser diode. As FIG. 5 shows, the thermal contacting portion (flange) 31 of the coaxial type laser diode 11-a is fitted in a cabinet 32 with a screw 33 that is driven in a screw hole 34. The screw 33 is made of nonconductive material such as resin or acrylic. A

nonconductor 35 likewise made of resin, acrylic, or

Teflon, is provided between the cabinet 32 and the

flange 31, suppressing heat conduction to the cabinet

32. Moreover, the thermal contacting portion (i.e.,

5   heat conducting portion, such as heat radiating

portion) of the heat source transistor 17 is adhered to

the flange 31. The flange 31 is grounded often. In

view of this, it is desired that the thermal conducting

portion of the transistor 17 be used as the grounding

10   electrode. In such a configuration, the heat

conduction from the coaxial type laser diode 11-a to

the cabinet 32 can be controlled, whereby the heat of

the transistor 17 is effectively conducted to the

coaxial type laser diode 11-a, with a minimum

15   dissipation of heat. It is, therefore, possible to

change the wavelength of the coaxial type laser diode

11-a using a transistor with small power dissipation.

Additionally, the flange 31 may be adhered to the

thermister 19 for measuring the temperature of the

20   coaxial type laser diode 11-a. Then, the thermister 19

can readily respond to changes in temperature of the

coaxial type laser diode 11-a, to measure the

temperature accurately.

FIG. 6 shows a specific example having a Mini-DIL

25   type package 11-b that contains a laser diode. The

laser diode 11-b has a heat-conducting portion on a

second main surface that is opposite to a first main

surface facing a board 39. The heat source transistor
17 and the thermister 19 are fixed to the heat-
conducting portion. The Mini-DIL type laser diode 11-b
is disposed between the board 39 and the transistor 17.

5   The board 39 can radiate heat efficiently. The heat of
the transistor 17 can therefore be conducted to the
Mini-DIL type laser diode 11-b, dissipating much heat
to the board 39.

In the exothermic temperature control method, the

10   temperature of the laser diode 11 cannot be stabilized
but to the preset temperature value higher than an
ambient temperature of the laser diode 11. The method
differs, in this respect, from the exothermic-and-
endothermic-effects control method. The exothermic-

15   effect-only temperature control method according to
this embodiment will be described below in detail.

If the preset temperature value 108 is
sufficiently higher than the ambient temperature of the
slave station 2, the temperature of the laser diode 11

20   will follow the preset temperature value 108. If the
ambient temperature of the slave station 2 is higher
than the preset temperature value 108, the temperature
of the laser diode 11 will follow the ambient
temperature. The temperature of the laser diode 11,

25   therefore, deviates from the preset temperature value
108 and is no longer subjected to wavelength control.
The temperature 107 measured agrees with the preset

temperature value 108 if subjected to the wavelength

control. If not subjected to the wavelength control

due to a rise in ambient temperature of the slave

station 2, the temperature 107 is that of the laser

5   diode, which has followed the ambient temperature. The

ambient temperature is considered nearly equal to the

temperature measured of the laser diode 11. The state

of wavelength control can be determined from the

relationship between the preset temperature value 108

10   and the temperature 107 measured. These two wavelength

states are set in the wavelength control of the present

invention. The wavelength control can therefore be

performed in several ways.

The wavelength control aims at avoiding the

15   influence of the optical beat noise. Hence, no

problems will arise even if the wavelength λ can no

longer controlled and may depend on the ambient

temperature, provided that the optical beat noise

imposes no influence on the signal 106 received. The

20   wavelengths of the optical signals 102 may be close to

each other and it may be necessary to conduct

wavelength control to avoid the influence of the

optical beat noise. In this case, the wavelength

controller 18 needs to set the preset temperature value

25   108 higher than the temperature 107 actually measured.

There is another wavelength control method, in

which the preset temperature value 108 is sufficiently

higher than the ambient temperature of the laser diode. This method can prevent the laser diode 11 from getting out of wavelength control. If the slave station 2 is installed indoors and the ambient temperature is

5   therefore stable, the temperature of the laser diode 11 can be easily stabilized at the preset temperature value 108. In view of this, very different wavelengths λ may be set for the slave stations 2 at the initial operation of the system or at every inspection thereof.

10   Then, no optical beat noise may appear in the band of the received signal 106.

However, it is not rare in many cases for the laser diode 11 to have its oscillation wavelength λ changed due to aging. Moreover, when the slave station

15   2 is installed outdoors, the temperature of the laser diode 11 may greatly change due to fluctuations in ambient temperature of the slave station owing to the weather. A second embodiment can performs a wavelength control method for providing high reliability against

20   the fluctuations in wavelength owing to such factors is given by.

Second Embodiment

FIG. 7 shows a schematic block diagram of an optical transfer system according to the second

25   embodiment. The same elements as those of the first embodiment are indicated by the same reference numerals. The second embodiment provides a method for detecting

at the master station 1 whether the optical beam noise
is present so that based on the detected information
the wavelength λ of each slave station 2 may be
controlled.

At the master station 1, the received signal 106
received at the light receiver 15 is partially input to
a noise detector 24. The noise detector 24 detects the
presence or absence of the optical beat noise contained
in received signal 106. Assume that a change in
ambient temperature or aging has such an effect that
the wavelengths of any of the received signals 102-104
get close to each other gradually to thereby generate
optical beat noise. The optical beat noise, therefore,
is generated in a high frequency band toward the band
of the information signal of the received signal 106.
To detect the optical beat noise before it deteriorates
the transfer quality of the received signal 106, the
noise detector 24 monitors the presence or absence of
the optical beat noise with reference to a noise-amount
threshold value preset in a band higher than that of
the optical beat noise. If there is no optical beat
noise detected, control is not conducted on the
wavelength λ of the laser diode 11 of each slave
station 2. If optical beat noise is detected, on the
other hand, to suppress it, control is conducted on the
wavelengths λ of the laser diodes 11 of the slave
stations 2 independently of each other or at a time.

The noise detector 24 generates a wavelength control
signal 111 for controlling the wavelength of the slave
station 2. A modulator 5 converts an information
signal 112 on the downward link into a modulated signal
and also superimposes the wavelength control signal 111
on it to provide a downward signal 114. If the
information signal 112 is a radio signal, the modulator
5 conducts, for example, frequency conversion to assign
the information to each slave station 2 to thereby
superimpose the wavelength control signal 111 on a sub-
carrier. A light transmitter 6 converts the downward
signal 114 into an optical signal 113. The signal is
transferred from the master station 1 to the slave
station 2. The optical signal 113 is transferred to
each slave station 2 via the optical 3a and the optical
coupler 4.

Each slave station 2 receives at a light receiver
7 the optical signal 113 transferred from the master
station 1. The light receiver 7 outputs the downward
signal 114 sent from the master station 1. The signal
114 is supplied to a demodulator 8. The demodulator 8
extracts the information signal 112 and the wavelength
control signal 111 from the downward signal 114. The
wavelength control signal 111 is output to the
wavelength controller 18. The wavelength controller 18
controls the wavelength λ of the laser diode 11 based
on the wavelength control signal 111. The wavelength

control signal 111 carries the information of a
wavelength shift of, for example, "+0.15 nm" or "-0.10
nm". The side of the slave station 2 controls the
wavelength λ based on the wavelength control signal
111, thus avoiding the influence of the optical beat
noise. As described in conjunction with the first
embodiment, the wavelength shift information mentioned
above may be employed if the preset temperature value
108 in the wavelength controller 18 is sufficiently
higher than the ambient temperature of the slave
station 2. If the slave station 2 is installed
outdoors and the preset temperature value 108 is nearly
equal to the room temperature, the temperature of the
laser diode 11 may sometimes be higher than the preset
temperature value 108. To avoid this situation, the
slave station 2 is adapted to always set the preset
temperature value 108 higher than the temperature
measurement 107 of the laser diode 11.

Third Embodiment

If the master station 1 conducts concentrated
management of the wavelengths of the slave stations, it
must know the temperature of the laser diode of each of
the slave stations 2 in order to control the wavelength
accurately. A transfer system that enables such
control is described as the third embodiment.

FIG. 8 shows a schematic block diagram of the
optical transfer system according to the third

embodiment. The slave station 2a superimposes the temperature information signal 107 sent from the temperature measuring circuit 20 on the modulated signal 101 to then use these signals 101 and 107 in

5   order to drive the laser diode 11. The laser diode 11 outputs the optical signal 102 and transfers it to the master station 1. In the master station 1, the light receiver 15 receives the optical signal 105. The optical signals 102, 103, and 104 sent from the slave

10   stations 2 are multiplexed to be the optical signal 105. The signal 105 is converted to a signal 106 at the receiver 15.+ The signal 106 is output as divided into three signals. The three signals are supplied to a temperature information receiver 25, the noise detector

15   24, and the demodulator 16, respectively. The temperature information receiver 25 extracts the temperature information signal 107 sent from each slave station 2. The noise detector 24 detects presence/absence of the optical beat noise. If the

20   noise detector 24 detects no optical beat noise, it is unnecessary to control the wavelength of each slave station. If any optical beat noise is detected, the wavelength of each slave station 2 is controlled. A wavelength control signal generator 26 outputs the

25   wavelength control signal 111. The signal is used to determine a preset temperature value of each slave station 2 based on the information transferred from the

temperature information receiver 25 and the noise

detector 24. The modulator 5 superposes the

information signal 112 on the wavelength control signal

111, generating a downward signal 114, which is then

5   transferred to the slave station 2. In this step, the

wavelength control signal generator 26 knows

temperature information of the slave station 2

beforehand. Therefore, the generator 26 outputs

information of a preset temperature value higher than

10   the temperature of the laser diode 11. Therefore, the

situation that the ambient temperature of the slave

station 2 is higher than the preset temperature value

can be avoided. This prevents the wavelength

controller 18 from being disabled. The wavelength λ

15   of the slave station 2 can thereby be controlled

reliably.

Moreover, since the master station 1 knows the

temperature information, it can also know whether the

wavelength controller 18 of each slave station 2 is

20   functioning. This helps to achieve an advantage of

easy maintenance and management.

FIG. 9 shows an algorithm for controlling the

wavelength between the master station 1 and the slave

stations 2. A method used in this algorithm of FIG. 9

25   for using the noise detector 24 of the master station 1

to thereby determine any one of the slave stations 2

that is concerned with the occurrence of optical beat

noise is disclosed, for example, in U.S. Patent

Application No. 09/243121 applied on February 3, 1992.

A major difference is that the wavelength control flow

starts with a step of shifting the wavelength to a

5   longer side so that the wavelength can be conducted

accurately even if the ambient temperature of the slave

station 2 is higher than a preset temperature value.

The noise detector 24 in the master station 1

monitors optical beat noise (hereinafter called OBI:

10   Optical Beat Interference) periodically and, if the

amount of the OBI becomes more than a threshold value

(hereinafter abbreviated as Vth), enters a flow for

controlling the wavelength of the slave station 2

(S100). Each slave station 2 is assigned its own

15   specific frequency band for sub-carrier multiplexing.

The master station 1 detects a frequency component

contained in the OBI (S110) to identify, based on the

detection result, slave stations 2 i and 2 i+1 (S120).

The master station 2 selects either one of these slave

20   stations 2. It is here supposed that the slave station

2 i+1 is selected. The master station 1 sets a preset

temperature value for the slave station 2 i+1 higher

than the temperature of the laser diode of the slave

station 2 i+1 (S130), to control the wavelength

25   securely. The master station 1 then transfers the

wavelength control signal 111 to the slave station 2

i+1 to then shift the wavelength of the slave station 2

i+1 to a longer side (S140). A wavelength shift amount
dλ is 0.05 nm, for example. The magnitude of the
wavelength shift amount dλ only needs to mitigate the
OBI and, not to generate new OBI with other slave
stations 2. As will be described later, the amount of
the OBI has little effect if the inter-wavelength
spacing is not less than 0.16 nm. To detect the OBI,
it is optimal to first search for the spacing of 0.16
nm or so where the OBI amount starts to change. At a
larger wavelength difference, the OBI amount levels off
at -140 dB/Hz or less, thus making it possible to
detect the occurrence of OBI. If the OBI is detected
and the wavelength is shifted by dλ supposed to be
0.05 nm, the inter-wavelength spacing becomes 0.11 nm
or 0.21 nm. If the inter-wavelength spacing between
the slave stations 2 i and 2 i+1 becomes 0.21 nm, the
OBI is suppressed down sufficiently. Additionally, if
it is 0.11 nm, the OBI becomes large in amount but of
such a value of -130 dB/Hz, still not goring so far as
to have a catastrophic influence on the transfer
quality of the received signal 106. The magnitude of d
λ = 0.05 nm is, therefore, appropriate but may be any
other value. When the wavelength is shifted, the OBI
is measured by the noise detector (S150, S160). If the
OBI is decreased in level to Vth or less, the control
flow ends (S170). If the OBI is indeed decreased but
still not less than Vth, new OBI may have occurred with

any other slave stations 2, so that the process
identifies again such slave stations that are concerned
with the occurrence of the OBI (S180). If no OBI-
concerned slave station 2 is detected newly, the
process shifts the wavelength of the slave station 2
i+1 to a longer side again (to S140). If a new OBI-
concerned slave station 2 i+2 is detected, on the other
hand, it is decided to be due to OBI with the slave
station 2 i+1 as wavelength-shifted, the process goes
along a wavelength control flow with the slave stations
2 i+1 and 2 i+2 (to S120). In FIG. 9, variables of 2
i+1 and 2 i+2 are exchanged with variables 2 i and 2
i+1 in the case (a). If the OBI is increased in level,
on the other hand, there are two possible cases. First,
the slave station 2 i+1 has generated OBI with a slave
station 2 i+2 other than the slave station 2 i. Second,
the slave stations 2 i and 2 i+1 have got close to each
other in wavelength. When the OBI has increased,
therefore, the process first identifies a slave station
2 concerned with the OBI (S190). If an OBI-concerned
slave station 2 is detected newly, the first case
applies. In the first case, it is necessary to reduce
the level of the OBI of the slave stations 2 i+1 and 2
i, so that the wavelength of the slave station 2 i+1 is
to be left as shifted. Then, the wavelength of the
slave station 2 i+2 is to be shifted to a longer side.
FIG. 9 shows a situation where the slave stations 2 i+1

and 2 i+2 are exchanged with the slave stations 2 i and
2 i+1 in the case (a) to then repeat a wavelength
control flow.

If no new OBI-concerned slave station 2 is
detected, the second case applies. That is, the
shifted wavelength of the slave station 2 i+1 is
restored to an original set value, and the wavelength
of the slave station 2 i is then shifted to a longer
side. This flow is indicated by an asterisk (*) in FIG.
9. For the wavelength of the slave station 2 i, the
other slave station 2 i+2 may occur new OBI. If so, it
is necessary to shift the wavelength of the slave
station 2 i+2. FIG. 9 shows that the variable (i, i+2)
is exchanged with (i, i+1) after the control flow
indicated by the asterisk (*) when a new OBI-concerned
slave station 2i+2 is identified. That is, the process
may goes through S200 and then, for example, S150, S190,
and back to S120 in this order or S150, S160, S180, and
back to S120 in this order. In this case, the subject
slave station changes from (i, i+2) to (i, i+1). If
the process does not pass through S200, the subject
slave station is changed from (i+1, i+2) to (i, i+1).
The wavelength control algorithm may be any other than
that shown in FIG. 9.

FIG. 10 shows a relationship between an inter-
wavelength spacing $\Delta \lambda$ [nm] of an optical signal output
from two slave stations and ROBIN (Relative Optical

Beat Interference Noise). Note that ROBIN indicates

the magnitude of OBI [dB/Hz] using the OMI (Optical

Modulation Index) of the laser diode as a parameter.

The inventor measured ROBIN in the case where each

laser diode is modulated with a sine-wave signal with a

frequency of 100MHz or HOMHz in a 1GHz band. As seen

from FIG. 10, the OBI amount increased with the

decreasing amount of $\Delta\lambda$. If a negligible level of the

influence of the OBI amount is -140dB/Hz as a ROBIN

equivalent of the laser diode, $\Delta\lambda$ must be 0.16nm or

higher even if a change difference in the ROBIN

corresponds to the OMI. The temperature dependency of

the laser diode wavelength is 0.1nm/℃ typically. Even

in the case where the output wavelengths of all the

laser diodes agree, the OBI can be avoided by giving a

temperature difference of 1.6℃ or higher between the

laser diodes. It only needs to give a temperature

difference of at least 1.6℃ for two slave stations, at

least 4.8℃ for four slave stations, and at least 12.8℃

for eight slave stations. Further, in a passive

optical network, the wavelengths of the slave stations

need not be evenly spaced. Therefore, it is sufficient

for the wavelength controller to give a wavelength

variation of 0.16nm or larger in inter-wavelength

spacing. In view of this, a small-power transistor can

be used, which can raise the ambient temperature by

1.6℃ or higher.

The first through third embodiments described above comprise the exothermic-effect-only heat source 17 that controls the wavelength of the laser diode 11. Nonetheless, an endothermic-effect-only wavelength controller may be employed to accomplish unidirectional control of the temperature. A method of only absorbing heat from the laser diode 11 may be performed, for example, by supplying only an unidirectional current into a Peltier element whose heat-absorbing surface faces the laser diode 11. Alternatively, this method may be performed by using an inverter-equipped fan that opposes the laser diode 11 to suppress a rise in temperature of the laser diode. The heating element employed may be, for example, a nichrome wire. Furthermore, if the information signal 100 is a bursting radio signal which fluctuates in intensity, the OMI of the laser diode 11 may possibly fluctuate over a range wider than that of 0.0 through 1.0. As shown in FIG. 10, however, the OBI is not dependent on the OMI and, in fact, behaves mostly in such a way that $\Delta\lambda$ increases from a vicinity of 0.16nm. Thus, the first through third embodiments of the present invention are applicable.

The above-mentioned embodiments employ a coaxial-type or Mini-DIL type package containing the laser diode. Nevertheless, the present invention is not limited to the embodiments. For example, any package

of a simple configuration may be applicable that
packages the laser diode only.

Additional advantages and modifications will
readily occur to those skilled in the art. Therefore,
the invention in its broader aspects is not limited to
the specific details and representative embodiments
shown and described herein. Accordingly, various
modifications may be made without departing from the
spirit or scope of the general invention concept as
defined by the appended claims and their equivalents.